

ASME B18.24-2020
(Revision of ASME B18.24-2015)

Part Identifying Number (PIN) Code System Standard for B18 Fastener Products

AN AMERICAN NATIONAL STANDARD



**The American Society of
Mechanical Engineers**

ASME B18.24-2020
(Revision of ASME B18.24-2015)

Part Identifying Number (PIN) Code System Standard for B18 Fastener Products

AN AMERICAN NATIONAL STANDARD



**The American Society of
Mechanical Engineers**

Two Park Avenue • New York, NY • 10016 USA

Date of Issuance: October 30, 2020

This Standard will be revised when the Society approves the issuance of a new edition.

ASME issues written replies to inquiries concerning interpretations of technical aspects of this Standard. Interpretations are published on the Committee web page and under <http://go.asme.org/InterpsDatabase>. Periodically certain actions of the ASME B18 Committee may be published as Cases. Cases are published on the ASME website under the B18 Committee Page at <http://go.asme.org/B18committee> as they are issued.

Errata to codes and standards may be posted on the ASME website under the Committee Pages to provide corrections to incorrectly published items, or to correct typographical or grammatical errors in codes and standards. Such errata shall be used on the date posted.

The B18 Committee Page can be found at <http://go.asme.org/B18committee>. There is an option available to automatically receive an e-mail notification when errata are posted to a particular code or standard. This option can be found on the appropriate Committee Page after selecting "Errata" in the "Publication Information" section.

ASME is the registered trademark of The American Society of Mechanical Engineers.

This code or standard was developed under procedures accredited as meeting the criteria for American National Standards. The Standards Committee that approved the code or standard was balanced to assure that individuals from competent and concerned interests have had an opportunity to participate. The proposed code or standard was made available for public review and comment that provides an opportunity for additional public input from industry, academia, regulatory agencies, and the public-at-large.

ASME does not "approve," "rate," or "endorse" any item, construction, proprietary device, or activity.

ASME does not take any position with respect to the validity of any patent rights asserted in connection with any items mentioned in this document, and does not undertake to insure anyone utilizing a standard against liability for infringement of any applicable letters patent, nor assume any such liability. Users of a code or standard are expressly advised that determination of the validity of any such patent rights, and the risk of infringement of such rights, is entirely their own responsibility.

Participation by federal agency representative(s) or person(s) affiliated with industry is not to be interpreted as government or industry endorsement of this code or standard.

ASME accepts responsibility for only those interpretations of this document issued in accordance with the established ASME procedures and policies, which precludes the issuance of interpretations by individuals.

No part of this document may be reproduced in any form,
in an electronic retrieval system or otherwise,
without the prior written permission of the publisher.

The American Society of Mechanical Engineers
Two Park Avenue, New York, NY 10016-5990

Copyright © 2020 by
THE AMERICAN SOCIETY OF MECHANICAL ENGINEERS
All rights reserved
Printed in U.S.A.

CONTENTS

Foreword		vi
Committee Roster		vii
Correspondence With the B18 Committee		viii
1	Introductory Notes	1
2	General Guidance	1
3	PIN Code Structure	2
Tables		
1-1	Fastener Family and Type/Base PIN	4
2-1	Thread Type	25
2-2	Thread and Point Options for Tapping Screws	25
3-1	Inch Thread	25
3-2	Inch Size	25
3-3	Metric Thread	26
3-4	Metric Size	27
3-5	Miniature Screw Thread	28
3-6	Inch Tapping Screw Thread	28
3-7	Metric Tapping Screw Thread	29
3-8	Inch Hex Socket Head Shoulder Screw Size	29
3-9	Metric Hex Socket Head Shoulder Screw Size	29
3-10	Inch Spline Socket Set Screw Thread	29
3-11	Inch Trim Head Machine Screw Size	29
3-12	Inch Wood Screw Thread	30
3-13	Inch Lag Screw Thread	30
3-14	Inch Rivet Size Weight	30
3-15	Inch Rivet Size Number	30
3-16	Inch Rivet Size 1	30
3-17	Inch Rivet Size/Length	30
3-18	Inch Pin Size 1	31
3-19	Inch Pin Size 2	31
3-20	Retaining Ring Size Number	31
3-21	Inch Retaining Ring Size	33
3-22	Inch Washer Size 1	34
3-23	Inch Washer Size 2	35
3-24	Inch Washer Size 3	35
3-25	Inch Washer Size 4	36
3-26	Metric Washer Size 1	36
3-27	Metric Washer Size 2	37
3-28	Metric Key Size 1	37
3-29	Metric Key Size 2	38
4-1	Inch Length/Other	38
4-2	Metric Length/Other	40
4-3	Inch Miniature Screw Length	41
4-4	Insert Length	42
4-5	Inch Pin Length	42
4-6	Inch Eyebolt Full Thread Length	42
5-1	Material and Treatment: ASTM Material Specifications	43
5-2	Material and Treatment: UNS Carbon and Alloy Steels	82
5-3	Material and Treatment: UNS Heat and Corrosion Resisting Steels	88

5-4	Material and Treatment: UNS Nonferrous Materials	93
5-5	Material and Treatment: SAE Material Specifications	96
5-6	Material and Treatment: ISO Material Specifications	97
5-7	Material and Treatment: IFI Material Specifications	98
5-8	Material and Treatment: B18.16.1M	98
5-9	Material and Treatment: B18.6.6	98
6-1	Plating, Coating, and Passivation: Plain, Unfinished	99
6-2	Plating, Coating, and Passivation: ASTM Finish Specifications	99
6-3	Plating, Coating, and Passivation: Government Finish Specifications	117
6-4	Plating, Coating, and Passivation: SAE Finish Specifications	118
6-5	Plating, Coating, and Passivation: ISO Finish Specifications	119
7-1	Plain: No Additional Features	120
7-2	Miscellaneous Features for Externally Threaded Fasteners	120
7-3	General Point Options	120
7-4	Features for Metric Flange Screws	120
7-5	Features for Metric 12-Spline Screws	120
7-6	Neck Options for Large Rivets	120
7-7	Cotter Pin Type	120
7-8	Pin Type	120
7-9	SEMs Washer Components	120
7-10	Wood Screw Thread Types	120
7-11	Miscellaneous Features for Socket Head Cap Screws	121
7-12	Self-Locking Elements for Set Screws	121
7-13	Thread Class for Track Bolts and Nuts	121
7-14	Alternate Points for Thumb and Wing Screws (ASME B18.6.8)	121

Nonmandatory Appendices

A	B18.24.1, B18.24.2, and B18.24.3 PIN Succession Instructions	123
B	B18.24.1, B18.24.2, and B18.24.3 PIN Succession Tables	128
C	Part Identifying Number System for Bent Bolts per ASME B18.31.5	172

Figures

A-1	Instructions	124
C-1	Part Identification Number (PIN) System for Bent Bolts	173

Tables

B-1	Fastener Family	128
B-2	Fastener Type: Externally Threaded	128
B-3	Fastener Type: Internally Threaded and Nonthreaded	142
B-4	Thread Series: Externally Threaded	143
B-5	Thread Series: Internally Threaded	143
B-6	Inch Size: Externally Threaded	143
B-7	Inch Size: Internally Threaded	143
B-8	Metric Size: Externally Threaded	144
B-9	Metric Size: Internally Threaded	144
B-10	Inch Miniature Screw Size	144
B-11	Inch Length: Externally Threaded	144
B-12	Metric Length: Externally Threaded	144
B-13	Inch Miniature Screw Length	145
B-14	Length: Internally Threaded	145
B-15–B-133	Dimensions/Other Characteristics: Nonthreaded	145
B-134	Material and Treatment A	160
B-135	Material and Treatment B	163
B-136	Plating, Coating, and Passivation	165
B-137	Additional Features: Externally Threaded	166
B-138	Additional Features: Internally Threaded	166
B-139	Additional Features: Nonthreaded	166
B-140	Cross Reference: Table 2-2 Tapping Screw Point AB	166

B-141	Cross Reference: Table 2-2 Tapping Screw Point B	166
B-142	Cross Reference: Table 2-2 Tapping Screw Point BF	166
B-143	Cross Reference: Table 2-2 Tapping Screw Point BP	167
B-144	Cross Reference: Table 2-2 Tapping Screw Point BT	167
B-145	Cross Reference: Table 2-2 Tapping Screw Point C	167
B-146	Cross Reference: Table 2-2 Tapping Screw Point D	167
B-147	Cross Reference: Table 2-2 Tapping Screw Point F	167
B-148	Cross Reference: Table 2-2 Tapping Screw Point G	167
B-149	Cross Reference: Table 2-2 Tapping Screw Point T	167
B-150	Cross Reference: Table 2-2 Tapping Screw Point U	167
B-151	Bridge to Table 3-6 for AB, B, BF, BP, BT	167
B-152	Bridge to Table 3-6 for C, D, F, G, T	167
B-153	Bridge to Table 3-7 for AB, B, BF, BT	167
B-154	Bridge to Table 3-7 for D, F, T	167
B-155	Bridge to Table 3-10	167
B-156	Bridge to Table 3-12	167
B-157	Bridge to Table 3-13	167
B-158	Cross Reference: Table 7-9 Washer Component 1	167
B-159	Cross Reference: Table 7-9 Washer Component 2	167
B-160	Cross Reference: Table 7-9 Washer Component 3	167
B-161	Cross Reference: Table 7-9 Washer Component 4	167
B-162	Cross Reference: Table 7-9 Washer Component 5	167
B-163	Cross Reference: Table 7-9 Washer Component 6	167
B-164	Cross Reference: Table 7-9 Washer Component 7	167
B-165	Cross Reference: Table 7-9 Washer Component 8	167
B-166	Cross Reference: Table 7-9 Washer Component 9	168
B-167	Cross Reference: Table 7-9 Washer Component 10	168
B-168	Cross Reference: Table 7-9 Washer Component 11	168
B-169	Cross Reference: Table 7-9 Washer Component 12	168
B-170	Bridge to Table 3-11	168
B-171	Bridge to Table 3-4	168
B-172	Bridge to Table 7-10	168
B-Index	B18.24 Legacy Table References From B18.24.1, B18.24.2, and B18.24.3	168
C-1	Materials for Bent Bolts	174
C-2	Finish Designations for Bent Bolts	175

FOREWORD

A joint government and ASME B18 meeting was held November 4, 1977 at Defense Industrial Supply Center in Philadelphia, Pennsylvania. A planning group was established to eliminate road blocks to the government acceptance and use of national voluntary standards. Designated the Ad Hoc Fastener Planning Group, the Group's first meeting was held February 2, 1978 at ASTM Headquarters in Philadelphia. At the meeting, government appendices to ASME B18 metric product standards were endorsed. In addition, an ANSI metric log was established to prevent duplicate efforts and provide the latest status of 18 metric fastener projects. The U.S. Army Armament Research Development and Engineering Center was tasked to provide government appendices for metric fastener standards on an as-needed basis.

At the ASME B18 Standards Committee meeting on December 5, 1991, based on a B18 Subcommittee 24 suggestion, the B18 Standards Committee unanimously approved a motion that Subcommittee 24 Industry/Government Liaison be reactivated and tasked by B18 to address the issue of how to best handle needed changes to the various government appendices.

At the Subcommittee 24 meeting, May 12, 1993 at ASME Headquarters in New York City, the part identifying number (PIN) code system concept for B18 product standards was agreed to. The need was expressed that a PIN code system be made available for all users, not just limited to government users. This was based on the recognition that twenty-eight B18 metric and one B18 inch (ANSI B18.2.1) standards contained government Appendices for Department of Defense (DOD) PIN acquisition usage and were not considered part of the B18 Standard. Again, the premise based on the aforementioned proposal was to provide a B18 code system for all users without exception.

Based on the B18 Standards Committee mandate, a Subcommittee 24 Task Group was formed to develop B18.24.1 (externally threaded fasteners) first, then proceed with B18.24.2 (internally threaded B18 fasteners) and B18.24.3 (nonthreaded fasteners) standards.

During the April 2003 B18 Subcommittee 24 and B18 Standards Committee meetings, it was agreed to draft a new standard, ASME B18.24, Part Identifying Number (PIN) Code System Standard for B18 Fastener Products, to replace the existing ASME B18.24.1, B18.24.2, and B18.24.3 standards. This was based on users' expressed need to reduce the 21-digit PIN code to a code with 18 digits, to accommodate the 18-digit maximum file name length constraint inherent with widely used computer aided design (CAD) software platforms. ASME B18.24-2004 was approved by the American National Standards Institute (ANSI) on April 16, 2004.

Following approval by the ASME B18 Standards Committee and after public review, ASME B18.24a-2006 was approved by the American National Standards Institute on December 7, 2006. The title of Table 1-1 was revised along with the column head under "Feature." Material was added under B18.2.6 and B18.9. "B18.16M" was revised to read "B18.16.3M." "B18.27.6" was revised to read "B27.6." "B18.27.7M" was revised to read "B27.7." "B18.27.8M" was revised to read "B27.8." Various changes were made throughout the document to incorporate required changes.

In 2013, Subcommittee 24 of the B18 Standards Committee created a Task Group to review the B18.24 document against new standards published since 2004 and revisions to existing standards. Quite a few changes were integrated into the new version including the addition of several commonly used ISO callouts for material and plating and several metric standards that had not previously existed. Several ASTM documents for material and plating were added to the B18.24 PIN system to make it more useful.

The 2015 edition was approved by ANSI as an American National Standard on June 1, 2015.

In this 2020 edition, Note (1) of Table 6-2 has been deleted and Table 6-3 has been revised to include MIL-PRF-32647, Zinc-Nickel Electroplating for Fasteners. The 2020 edition was approved by ANSI as an American National Standard on July 6, 2020.

ASME B18 COMMITTEE

Standardization of Bolts, Nuts, Rivets, Screws, Washers, and Similar Fasteners

(The following is the roster of the Committee at the time of approval of this Standard.)

STANDARDS COMMITTEE OFFICERS

W. Guth, *Chair*
J. Medcalf, *Vice Chair*
A. L. Guzman Rodriguez, *Secretary*

STANDARDS COMMITTEE PERSONNEL

T. Anderson , Bay Bolt	C. B. Williamson , Fastenal Co.
L. Borowski , Greenslade and Co., Inc.	J. F. McCarrick , <i>Alternate</i> , Defense Supply Center Philadelphia
S. Brahimi , Industrial Fasteners Institute	M. Byrne , <i>Contributing Member</i> , General Fasteners Co.
B. Cao , Infasco	R. W. Davidson , <i>Contributing Member</i> , Endries International
V. Cartina , HI-Performance Fastening Systems	J. J. Grey , <i>Contributing Member</i> , Fastener Consulting Services, Inc.
L. Claus , NNI Training and Consulting, Inc.	J. C. Jennings , <i>Contributing Member</i> , Naval Surface Warfare Center
A. P. Cockman , Consultant	M. Kaindl , <i>Contributing Member</i> , Aztech Locknut Co.
D. S. George , Michigan Metal Coating	D. Korneffel , <i>Contributing Member</i> , CADENAS PARTsolutions
W. Guth , Electric Boat Corp.	J. J. Stoczanskyj , <i>Contributing Member</i> , Beacon Fasteners and Components, Inc.
J. Medcalf , Field Fastener	R. D. Strong , <i>Contributing Member</i> , Lear Corp.
M. Q. Muhammad , Defense Logistics Agency Troop Support	C. G. Vertullo , <i>Contributing Member</i> , Carver Engineering and Manufacturing
J. P. Nash , Caterpillar, Inc.	C. J. Wilson , <i>Contributing Member</i> , Consultant
F. J. Perry , John Deere	
A. L. Guzman Rodriguez , The American Society of Mechanical Engineers	

B18 SUBCOMMITTEE 24 — PIN CODE SYSTEM FOR B18 FASTENERS

D. Korneffel , <i>Chair</i> , CADENAS PARTsolutions	M. Keller , CADENAS PARTsolutions
A. P. Cockman , Consultant	M. Q. Muhammad , Defense Logistics Agency Troop Support
J. P. Fragnoli , General Fasteners Co.	J. F. McCarrick , <i>Alternate</i> , Defense Supply Center Philadelphia
B. Hasiuk , Defense Supply Center Philadelphia	C. J. Wilson , <i>Contributing Member</i> , Consultant
J. C. Jennings , Naval Surface Warfare Center	

CORRESPONDENCE WITH THE B18 COMMITTEE

General. ASME Standards are developed and maintained with the intent to represent the consensus of concerned interests. As such, users of this Standard may interact with the Committee by requesting interpretations, proposing revisions or a case, and attending Committee meetings. Correspondence should be addressed to:

Secretary, B18 Standards Committee
The American Society of Mechanical Engineers
Two Park Avenue
New York, NY 10016-5990
<http://go.asme.org/Inquiry>

Proposing Revisions. Revisions are made periodically to the Standard to incorporate changes that appear necessary or desirable, as demonstrated by the experience gained from the application of the Standard. Approved revisions will be published periodically.

The Committee welcomes proposals for revisions to this Standard. Such proposals should be as specific as possible, citing the paragraph number(s), the proposed wording, and a detailed description of the reasons for the proposal, including any pertinent documentation.

Proposing a Case. Cases may be issued to provide alternative rules when justified, to permit early implementation of an approved revision when the need is urgent, or to provide rules not covered by existing provisions. Cases are effective immediately upon ASME approval and shall be posted on the ASME Committee web page.

Requests for Cases shall provide a Statement of Need and Background Information. The request should identify the Standard and the paragraph, figure, or table number(s), and be written as a Question and Reply in the same format as existing Cases. Requests for Cases should also indicate the applicable edition(s) of the Standard to which the proposed Case applies.

Interpretations. Upon request, the B18 Standards Committee will render an interpretation of any requirement of the Standard. Interpretations can only be rendered in response to a written request sent to the Secretary of the B18 Standards Committee.

Requests for interpretation should preferably be submitted through the online Interpretation Submittal Form. The form is accessible at <http://go.asme.org/InterpretationRequest>. Upon submittal of the form, the Inquirer will receive an automatic e-mail confirming receipt.

If the Inquirer is unable to use the online form, he/she may mail the request to the Secretary of the B18 Standards Committee at the above address. The request for an interpretation should be clear and unambiguous. It is further recommended that the Inquirer submit his/her request in the following format:

- Subject: Cite the applicable paragraph number(s) and the topic of the inquiry in one or two words.
- Edition: Cite the applicable edition of the Standard for which the interpretation is being requested.
- Question: Phrase the question as a request for an interpretation of a specific requirement suitable for general understanding and use, not as a request for an approval of a proprietary design or situation. Please provide a condensed and precise question, composed in such a way that a “yes” or “no” reply is acceptable.
- Proposed Reply(ies): Provide a proposed reply(ies) in the form of “Yes” or “No,” with explanation as needed. If entering replies to more than one question, please number the questions and replies.
- Background Information: Provide the Committee with any background information that will assist the Committee in understanding the inquiry. The Inquirer may also include any plans or drawings that are necessary to explain the question; however, they should not contain proprietary names or information.

Requests that are not in the format described above may be rewritten in the appropriate format by the Committee prior to being answered, which may inadvertently change the intent of the original request.

Moreover, ASME does not act as a consultant for specific engineering problems or for the general application or understanding of the Standard requirements. If, based on the inquiry information submitted, it is the opinion of the Committee that the Inquirer should seek assistance, the inquiry will be returned with the recommendation that such assistance be obtained.

ASME procedures provide for reconsideration of any interpretation when or if additional information that might affect an interpretation is available. Further, persons aggrieved by an interpretation may appeal to the cognizant ASME Committee or Subcommittee. ASME does not “approve,” “certify,” “rate,” or “endorse” any item, construction, proprietary device, or activity.

Attending Committee Meetings. The B18 Standards Committee regularly holds meetings and/or telephone conferences that are open to the public. Persons wishing to attend any meeting and/or telephone conference should contact the Secretary of the B18 Standards Committee. Future Committee meeting dates and locations can be found on the Committee Page at <http://go.asme.org/B18committee>.

PART IDENTIFYING NUMBER (PIN) CODE SYSTEM STANDARD FOR B18 FASTENER PRODUCTS

1 INTRODUCTORY NOTES

1.1 Scope

1.1.1 This Standard is intended to provide all users (manufacturers, distributors, design and configuration, parts control, inventory control, test and maintenance functions) with the capability to identify externally threaded, internally threaded and nonthreaded fastener products by a preselected order of coding as specified herein.

1.1.2 The B18 PIN is a self-contained code, with distinct identification linkage to individual ASME B18 fastener product standards. The PIN code concept provides for direct traceability back to the applicable B18 product standard. In case of conflict with this document and the B18 product standard, the B18 product standard shall take precedence.

1.1.3 This Standard is not intended for use as a substitute for the correct usage of the B18 standards for fastener selection and specification. The PIN code is intended as an alternative to the plain text product callout as prescribed in the "Designation" or "Ordering" section of the source B18 product standard. The existence of a PIN code for B18 fastener description is not intended to imply that all products described are available.

1.1.4 A few B18 fasteners cannot be thoroughly identified using the 18-digit system defined in this Standard. If the user does not find the PIN needed in the body of this Standard, consult the Appendix where special PIN systems have been created to specifically identify those items. If the sought-after PIN for the desired B18 fastener is not in the Appendix, notice should be sent to the secretary of B18 so that the item can be addressed in the next revision of this Standard.

2 GENERAL GUIDANCE

2.1 Optional Coverage

Each individual ASME B18 fastener product standard provides for optional B18 PIN coverage under "Designation" or "Ordering" data.

2.2 Alpha "I" and "O"

Alpha "I", "O", and "-" are not used in PIN field coding configuration.

2.3 Characteristics

The B18 PIN code shall identify only those characteristics specified in the B18 product standards.

2.4 Succession of B18.24.1, B18.24.2, and B18.24.3 21-Character PIN Codes

Nonmandatory Appendices A and B of this document provide instructions and resources for determining the superseding B18.24.4 18-character PIN code for any cancelled B18.24.1, B18.24.2, and B18.24.3 21-character PIN code.

2.5 Identification of Part Numbering System on Drawings

On drawings or parts lists where a column exists for identifying the manufacturer or its Commercial and Government Entity Code, indicate the CAGE Code "05047/B18.24" or "ASME B18.24". If no column exists or there is space only for the five-digit CAGE Code, then a note must indicate that the part numbers are defined in ASME B18.24.

2.6 Guidance for Using B18.24

B18.24 (this Standard) defines an 18-digit alphanumeric system for describing most ASME B18 fasteners. Those using this Standard shall refer to the specific ASME B18 standard for product details first, and only then use the appropriate descriptive number defined in this Standard for placing inquiries and orders.

This Standard can be used to describe fasteners that are not readily available from suppliers, or to create numbers in conflict with the B18 product requirements, such as selecting inappropriate or non-recommended finishes. This is why it is critical for users to review the applicable B18 standard before using B18.24 to describe a desired fastener. The product requirements cited in individual ASME B18 Standards take precedence over conflicting numbers that might be created using B18.24.